



- Sandwich-Bauweise
- Geräuscharm
- Geringer Druckverlust
- Einbaulage beliebig
- Hohe Zuverlässigkeit
- Lange Lebensdauer
- Baulänge gemäß EN 558-1 Reihe 49 (DIN 3202-K4)

- Sandwich type
- Low noise
- Low pressure loss
- Any position of installation
- High reliability
- Long service life
- Face to face dimension acc. to EN 558-1 line 49 (DIN 3202-K4)

DN	125	150
ØA	194	220
ØB	112	132
ØC	166	195
D	90	106
ØE	140	160
kg	10	14

Teil Nr. Part no.	Bezeichnung	Description	Material	
			RF 6666 M	RF 6666 E
1	Gehäuse	Body	1.4408	1.4408
2	Ventilplatte	Valve plate	1.4408	1.4408
3	Führung	Support	1.4408	1.4408
4	Feder	Spring	1.4571	1.4571
5	O-Ring	O-Ring	—	EPDM (E) - NBR (B) FPM (V) - FEP/FPM (T)

Sonderausführungen in Titan, Hastelloy, Teflon, etc. auf Anfrage.
 Special executions in Titanium, Hastelloy, Teflon, etc. on request.

Änderungen vorbehalten
 Subject to changes.