P5/EP5 positioner order code

						PP5	PA5	EP5
A=	**Model no**							
	P	P	5	X	X	Double acting, pneumatic			
	P	A	5	X	X	Double acting, pneumatic ATEX II 1 GD			
	E	P	5	X	X	Double acting, electropneumatic			
	E	P	5	F	S	Double acting, electropneumatic Fail in last position			
	E	P	5	I	S	Double acting, electropneumatic, Intrinsically safe ATEX, IEC, CSA/FM			
	E	P	5	E	X	Double acting, electropneumatic, Explosion proof, ATEX, IEC, FM/CSA			
B=	**Spoolvalve**							
	H	P				High performance			
	L	B				Standard performance			
C=	**Connection threads**							
	G					1/4" G air, M20 x 1,5 electrical			
	N					1/4" NPT air, 1/2" electrical			
	M					1/4" NPT air, M20 x 1,5 electrical			
D=	**Surface treatment**							
	U					Epoxy, ED			
	M					Tufram R66 (C=N only & F=D01 as default & Powder epoxy I/P on EP5)			(*)
E=	**Spindle (Sample shown only, more available)**							
	0	1				14 mm female			
	2	3				Rotary, Namur, VDI/VDE 3845			
F=	**Cam (Sample shown only, more available)**							
	K	0	1			Linear 90 deg			
	K	0	3			Linear 30/60 deg			
	D	0	1			Linear 90 deg, splined version (Default on Tufram)			
G=	**Frontcover (Sample shown only, more available)**							
	P	V	9			90 deg, 0-100% scale			
	P	V	6			60 deg, 0-100% scale			
	P	V	4			45 deg, 0-100% scale			
	P	V	3			30 deg, 0-100% scale			
	P	V	0			Blank, no scale			
H=	**Function**							
	D					Direct			
I=	**Indicator**							
	A					Indicator			
	B					Blind, No indicator			
	H					Dome style, H5			
J=	**Input signal**							
	3					3-15 psi			
	4					4-20 mA			
	6					6-30 psi			
	7					Non-interactive Span/Zero (3-15 psi or 4-20 mA) (not when A=EP5FS)			
K=	**Seals/Temperature**							
	Z					Nitrile, NBR -20 to +85 deg C			
	Q					Silicon, Q -40 to 85 deg C			(**)
	B					Gas sealed, w. Q Seals			

					-					-						-	P	V		D		-		
		5																						

(*) For EP5EX and EP5TX - ExIP part (PT32 or PT3R) are polyester coated

(**) IP internal seals are Nitrile